



30 RPE COEXTRUDED 30mil Reinforced Polyethylene

SPECIFICATION SHEET

Heavyweight fabric incorporating a special weave pattern to enhance thickness, flatness, and tear properties. This product is a combination of polyethylene reinforcement and co-extrusion which enhances UV Resistance and improves physical properties. For use in [geomembrane applications](#) such as soil remediation, [pond lining](#), [canal lining](#), [landfill covers](#), tank lining, etc.

PRODUCT SPECIFICATIONS

WEAVE	Woven black HDPE scrim
COATING	2.4 mil average each side + 5.5 mils of special LLDPE blend on one side
COLOR	Black
WEIGHT	14.7 oz/yd ² (SOS g/m ²) +/- 5%
THICKNESS	Nominal 30 mil (0.75 mm) +/- 10%ASTM01777

PRODUCT PERFORMANCE

GRAB TENSILE	Warp 345 1535 N	Weft 325 1445 N	ASTM 07-7004
TOUNGE TEAR	Warp 90 LB 400 N	Weft 90LB400 N	ASTM 05884-01
TRAPEZOIDAL TEAR	Warp 99 LB 440 N	Weft 81LB360 N	ASTM 04533-04
MULLEN BURST	· 650 psi 4480 kPa		ASTM 03786-01
HYDROSTATIC RESISTANCE	635 psi 4375kPa		ASTM 0751-00
PERMEABILITY	2.06x 10 ⁻¹² cm/sec		ASTM D4491-99a
PUNCTURE RESISTANCE INDEX	180LB800N		ASTM 04833-02

All information, recommendations and suggestions appearing in this literature concerning the use of our products are based upon test and data believed to be reliable; however, it is the user's responsibility to determine the suitability for their own use of the products described herein. Since the actual use by others is beyond our control, no guarantee or warranty of any kind, expressed or implied, is made by Carson MFG. as to the effects of such use or the results to be obtained, nor does Carson MFG. assume any liability in connection herewith. Any Statement made herein may not be absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. Nothing herein contained is to be construed as permission or as a recommendation to infringe any patent.